



## AL

# Fully Insulated Premium Passthrough Dishwasher – 500mm Rack **W 750mm x D 795mm x H 1530mm**

The Washtech Premium Range represents the most technologically advanced dishwashers in the Washtech line up. They are built to deliver the best wash results alongside the latest enhancements such as advanced electronic controllers, enhanced filtration and full thermal and acoustic insulation to provide an optimal operating environment around the machine. Our assured rinse system ensures constantly great rinsing every cycle, while the soft start functionality protects your glassware and crockery.

With a powerful wash pump and the shortest cycle of 40 seconds the Washtech AL is the perfect machine for fast paced kitchens that need a high powered machine designed to keep up with very busy operations.

#### **Standard Features**

- · Autostart on door closure 40, 60 and 90 second cycles
- Washes up to 1,620 plates per hour
- · Easy installation supplied complete with:
  - · Water supply hose
  - · Dual detergent and rinse aid pumps with injector lines
  - · Drain pump outlet hose
  - · No commissioning required
- Reliable results through robust stainless steel wash and rinse arms with precision stainless jets
- · Durable stainless steel construction
- · Moffat's Comprehensive 5-2-1 Warranty
- · Low hot water consumption of 2.4 litres per cycle
- Soft start ensures great results through progressively pressurising the cycle to provide a consistent and even clean every time
- EcoPower reduces temperatures and energy consumption when machine is not being used
- Full thermal and acoustic insulation (via dual stainless steel panelling) to provide a cooler and quieter operating environment
- Enhanced filtration system that allows you to drain straight from the keypad, with no need to put your hand in the machine

#### Includes:

- · 2 x 600 70028 500mm dish rack
- 1x 600 70029 500mm cup rack
- · 1x C660503 cutlery container
- 1x C660508 cutlery basket






















### Fully Insulated Premium Passthrough Dishwash

#### W 750mm x D 795mm x H 1530mm







(1) Bench gap 640
Corner Installation
(2) wall to front Inside corner of wash tank 740
(3) machine must face left for access to controls
(4) allow 300 clearance beneath bench to front for service access
(5) splashback return no higher than 150
(5) left side is mirror image



Temperature Connection 3/4" male hose supplied 200-350kPa Pressure

Flow 15 litres per min Potable & soft Backflow Prevention Dual Check Valve (DCV) Consumption 2.4 litres per cycle

B Waste

Connection Hose supplied for 38mm open standpipe 750 high

or connection to sink trap

C Electrical

Three phase 415V 50Hz 15A/phase

**Maximum Power Consumption** Three phase 9.0kW Heating

2 5k\\/ \\/ash Rinse 6.0kW Dimensions

(6)

Width 750mm 795mm Depth Height 1530mm Weight 120kg

**Packed Dimensions** 

800mm Width Depth 950mm Height 1475mm Weight 140kg Cubicmetres

Water Quality Requirements

рΗ Hardness ppm Min 20 Max 100 8 SO<sub>4</sub> Fe Mn Cu CL, Max mg/l 100 400 0.05 0.1 0.5

Refer operator manual for installation instructions





moffat.com.au

Australia Moffat Pty Limited

Victoria/Tasmania

740 Springvale Road Mulgrave, Victoria 3170 Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au www.moffat.com.au

New South Wales

Telephone 02-8833 4111 nswsales@moffat.com.au

South Australia

Telephone 03-9518 3888 vsales@moffat.com.au

Queensland

Telephone 07-3630 8600 qldsales@moffat.com.au

Western Australia

Telephone 08-9202 6820 bgarcia@moffat.com.au

ISO9001

All Washtech products are designed and manufactured by Washtech using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Washtech reserves the right to change specifications and design without notice.



© Copyright Moffat Ltd Moffat / 1116



