

HRE-70B UPRIGHT REACH IN REFRIGERATOR



<i>Product Specifications</i>	
<i>WEIGHT</i>	Net: 116kg / Packed: 131kg
<i>AC SUPPLY VOLTAGE</i>	220 - 240v / 50Hz / 1
<i>ELECTRIC CIRCUIT PROTECTION</i>	Earth Wire, Circuit Breaker
<i>INTERIOR / EXTERIOR</i>	Stainless Steel / Stainless Steel, Galvanized Steel (Rear, Bottom)
<i>AMPERAGE</i>	2.06A
<i>REFRIGERATION SYSTEM</i>	Forced Air Circulation Interior Fan - DC12V 4W x 1
<i>DEFROST SYSTEM</i>	Off-Cycle
<i>TEMPERATURE CONTROL</i>	Microprocessor (Digital temp. indication) - Adjustable from 0°C to 16°C
<i>DEFROST CONTROL</i>	Microprocessor
<i>DRAIN EVAPORATOR PAN</i>	Stainless steel, 170W
<i>CASTOR</i>	Urethane (76mm DIA, 115mm High)
<i>EFFECTIVE CAPACITY</i>	Approx. 631L
<i>INSULATION</i>	Polyurethane foam
<i>REFRIGERANT</i>	R134a
<i>HEAT REJECTION</i>	535W at 43°C ambient
<i>AMBIENT TEMPERATURE</i>	5 — 43°C

<i>Product Range</i>		
<i>PART NO.</i>	<i>DESCRIPTION</i>	<i>LIST PRICE</i>
97000001	HRE-70B	

HRE-70B UPRIGHT REACH IN REFRIGERATOR

