

ZIP HYDROTAP MINIBOIL B

Order Code HT1017

Zip HydroTap Miniboil, Boiling, Filtered water appliance featuring a stylish touch activated tap and a compact under bench command centre with externally mounted water filtration.

Manufacturing Code	2500AU0M2ZN1R
Capacity	Residential
Disability Options	Unavailable



Тар	Zip HydroTap Miniboil CLASSIC Tap (Chrome)
Water Pressure	Min 172kPa - Max 700kPa
Water Connection	12.7mm BSP
Water Supply Requirements	Cold
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Power Rating	1.5kW 220-240V 50/ 60 Hz
Power Supply	1 x 10Amp GP0
Dimensions	H338mm x W212mm x D269mm
Product Approvals	WaterMark, CE, RCM
Warranty	12 months

Installation Requirements

- "1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
- 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
- 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
- 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
- 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
- 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com"

Installation Detail

