



ECO2D
ECO2D Convection Oven

Solid-state thermostats for fast response
Recessed controls
Cool down switch allows rapid oven cool-down
Door opens full 180°
Stainless steel door liner & porcelain enamel oven cavity
Cool-to-the-touch door handle
Door interlock switch
Nine rack capacity
240/60/1 or 3 phase electrical supply
Dimensions w x d x h: 772 x 635 x 736mm



VC4E
VC4E Electric Heavy Duty Convection Oven

Oven cavity is 675mm deep
Stainless steel front & sides
655mm stainless steel legs
Auxiliary fan switch for rapid cool
60-minute electric timer with time expired buzzer
Cool-to-the-touch oven door handles
Two doors per section with 180° swing
Oven sideliners, door liners & fan cover are porcelain on steel
Stainless steel oven door gaskets
Five nickel plated racks
415/50/3 - 12.5kW Electrical Supply
Dimensions w x d x h: 1016 x 990 x 1441mm



VC6ED
VC6ED Electric Heavy Duty Convection Oven

Oven cavity is 775mm deep
Stainless steel front & sides
655mm stainless steel legs
Auxiliary fan switch for rapid cool
60-minute electric timer with time expired buzzer
Cool-to-the-touch oven door handles
Two doors per section with 180° swing
Oven sideliners, door liners & fan cover are porcelain on steel
Stainless steel oven door gaskets
Five nickel plated racks
415/50/3 - 12.5kW Electrical Supply
Dimensions w x d x h: 1016 x 1092 x 1441mm