



## Standard and Wide Entry Gastronorm Refrigeration

Stylish design offering a choice of wide entry or standard gastronorm design combined with an easy to use control panel for excellent temperature control



**Garnet**



**Sapphire**

### Benefits

- Tough, durable stainless steel exterior and choice of interior finishes
- All cabinets accommodate 1/1 and 2/1 pans
- Easy to clean, hygienic stainless steel base with radius corners and removable shelf supports and racking
- Top mounted removable refrigeration system for easy service and maintenance
- Designed for 43°C ambient environments
- Self closing lockable doors with easy to clean handles
- Heavy duty swivel and brake castors for easy mobility
- CFC free and designed and built to international quality standards
- HACCP compliant



## Sapphire / Garnet

For over 20 years Williams Refrigeration has been a leader in refrigeration technology and design, marketing refrigeration products worldwide. Manufacturing a wide range of products to international quality and construction standards, Williams has gained a global reputation for strength, quality and reliability.

### Features

Designed and manufactured to the highest specification meeting international quality standards, the cabinets offer stylish design with easy to clean moulded handles.

### Construction

- Tough stainless steel exterior and interior (except rear) for durability
- Self closing lockable doors, opening to 90° and easy to change magnetic seal
- Swivel and brake castors for easy positioning
- 75mm CFC free insulation

### Refrigeration

Leading the way in refrigeration technology, all Williams products are CFC free and designed for efficient and cost effective operation.

- Top mounted removable, forced air refrigeration for easy servicing and maintenance
- Automatic defrost - off cycle above +1°C
- Waste heat recovery vaporiser
- Digital temperature controller
- Anti condensation heaters on cabinets operating below 0°C
- 240 volt 50 cycle single phase unit complete with fitted plug



## Control Panel

Stylish, state of the art control panel incorporates many features to ensure excellent temperature control and effective, easy to manage operation even in the busiest environment.

Easy to operate buttons and clear LED display allow you to be in control

- Adjustable operating temperature for maximum effectiveness even in the hottest environment
- Auto/manual defrost and defrost indicator
- Compressor running indicator

**The cabinets continue to function even if the Control Probe fails**

## Options

- Glass doors and half doors
- Pass through facility
- Adjustable legs instead of castors





## Garnet Specifications

**G1T** Internal H1370mm x W587mm x D683mm



Model	Temp °C	Amp	Shelves	Net Cap Ltrs / Cu ft
<b>One Door</b>				
HG1T	+1 / +4	3.0	4	610/21
MG1T	-2 / +2	4.0	4	610/21
FG1T	-2 / +2	4.0	-	610/21
WG1T	+3 / +13	4.0	4	610/21
LG1T	-18 / -22	4.5	4	610/21
HLG1T	+1 / +4	6.0	2	290/10
	-18 / -22	4.5	2	290/10
CFG1T	0 / +3	4.0	4	610/10

**G2T** Internal H1370mm x W1249mm x D683mm



Model	Temp °C	Amp	Shelves	Net Cap Ltrs / Cu ft
<b>Two Door</b>				
HG2T	+1 / +4	4.0	8	1271/45
MG2T	-2 / +2	5.0	8	1271/45
WG2T	-3 / +13	5.0	8	1271/45
LG2T	-18 / -22	6.0	8	1271/45
HLG2T	+1 / +4	7.0	4	595/21
	-18 / -22	6.0	4	595/21
CFG2T	0 / +3	5.0	8	1271/45

**G3T** Internal H1370mm x W1249mm x D683mm



Model	Temp °C	Amp	Shelves	Net Cap Ltrs / Cu ft
<b>Three Door</b>				
HG3T	+1 / +4	7.0	12	2000/71
MG3T	-2 / +2	7.0	12	2000/71
LG3T	-18 / -22	9.0	12	2000/71
CFG3T	0 / +3	7.0	12	2000/71

## Sapphire Specifications

**S1T** Internal H1370mm x W715mm x D560mm



Model	Temp °C	Amp	Shelves	Net Cap Ltrs / Cu ft
<b>One Door</b>				
HS1	+1 / +4	3.0	4	595/21
MS1	-2 / +2	4.0	4	595/21
LS1	-18 / -22	4.5	4	595/21
CFS1	0 / +3	3.0	4	595/21

**S2T** Internal H1370mm x W1505mm x D560mm



Model	Temp °C	Amp	Shelves	Net Cap Ltrs / Cu ft
<b>Two Door</b>				
HS2	+1 / +4	4.0	8	1273/45
MS2	-2 / +2	3.5	8	1273/45
LS2	-18 / -22	6.0	8	1273/45
CFS2	0 / +3	3.5	8	1273/45

Installation of all cabinets require adequate ventilation

We reserve the right to change the specifications without notice



**Williams Refrigeration Australia Pty Ltd**

38-42 Gaine Rd Dandenong South Victoria 3175

Telephone: 03 9799 4900 Facsimile: 03 9799 4911 FreeCall: 1800 338 148

Email: wra@access.net.au www.williamsref.com.au ABN 25 006 630 084



AGA FOODSERVICE EQUIPMENT



## Lowline Refrigerator Range



### Jarrah

#### Benefits

- Standard drawer frame accommodates either 2 x 1/1 or 1 x 2/1 gastronorm pans in both models
- 304 grade stainless steel interior and exterior except rear and under
- Includes integral thermal insulating barrier to deflect heat from cooking unit
- Adjustable digital thermostat for flexible cooling and accuracy
- Self contained or remote cabinet
- Four drawer available remote only
- 100% CFC free polyurethane foam for greater insulation and added strength
- Rated for 43°C ambient working conditions.



### JL2R



### JL2U



### JL4R



Model	Temp°C	Amp	Pan Capacity
-------	--------	-----	--------------

**2 Drawer:** External dimensions 1030mm/1400mm x 650mm x 640mm

JL2R	+1/+4	0.5	2 x 1/1 per drawer
JL2U	+1/+4	2.5	2 x 1/1 per drawer

**4 Drawer:** External dimensions 1820mm x 650mm x 640mm

JL4R	+1/+4	0.3	2 x 1/1 per drawer
------	-------	-----	--------------------

Williams Refrigeration reserve the right to change specifications without notice.

## Controls

- Digital microprocessor control with adjustable electronic thermostat and defrost interval to ensure excellent temperature control.

## Construction

- Designed and manufactured to international quality standards
- Stainless steel interior and exterior except rear and under
- Pan holding frame standard
- Frame will accommodate 2 x 1/1 or 1 x 2/1 100mm deep gastronorm pans
- 2 x 1/1 100mm pans per drawer included
- Supplied on castors for mobility (reduces height by 30mm). Legs included for remote models.

## Refrigeration

### Self Contained (2 drawer only):

- Forced air refrigeration system
- 240 volt single phase power
- 43°C ambient operation
- Waste heat condensate tray

### Remote:

- Forced air refrigeration system
- 240 volt single phase power
- Left hand services only
- Supplied with evaporator, tx valve and digital thermostat
- Refrigerant pipes and drain exit out through rear of cabinet unless otherwise specified.

## Options

- Full drawer base available
- Locking tabs.



## Williams Refrigeration Australia Pty Ltd

38-42 Gaine Road Dandenong South Victoria Australia 3175

Telephone: 03 8787 4747 Facsimile: 03 8787 4787 FreeCall: 1800 338 148

Email: sales@williamsref.com.au www.williamsref.com.au ABN 25 006 630 084



**Opal / Emerald Specifications**



Model	Temp °C	Amp	Shelves
<b>O1U ONE DOOR 198 litres (7 cu.ft)</b> External dimensions 955mm x 650mm x 845mm. <u>For remote models 705mm x 650mm x 875mm.</u>			
HO1U	+1 / +4	3.0	2
MO1U	-2 / +2	3.0	2
LO1U	-18 / -22	4.0	2
<b>O2U TWO DOORS 350 litres (12.5 cu.ft)</b> External dimensions 1420mm x 650mm x 845mm. <u>For remote models 1170mm x 650mm x 875mm.</u>			
HO2U	+1 / +4	3.0	4
MO2U	-2 / +2	3.0	4
LO2U	-18 / -22	4.0	4
<b>O3U THREE DOORS 510 litres (18 cu.ft)</b> External dimensions 1885mm x 650mm x 845mm. <u>For remote models 1635mm x 650mm x 875mm.</u>			
HO3U	+1 / +4	3.5	6
MO3U	-2 / +2	3.5	6
LO3U	-18 / -22	4.5	6
<b>O4U FOUR DOORS 670 litres (24 cu.ft)</b> External dimensions 2350mm x 650mm x 845mm. <u>For remote models 2100mm x 650mm x 875mm.</u>			
HO4U	+1 / +4	3.5	8
MO4U	-2 / +2	3.5	8




Model	Temp °C	Amp	Shelves
<b>E1U ONE DOOR 310 litres (11 cu.ft)</b> External dimensions 1152mm x 773mm x 845mm. <u>For remote models 902mm x 773mm x 875mm.</u>			
HE1U	+1 / +4	3.0	2
ME1U	-2 / +2	3.0	2
LE1U	-18 / -22	4.0	2
<b>E2U TWO DOORS 623 litres (22 cu.ft)</b> External dimensions 1815mm x 773mm x 845mm. <u>For remote models 1565mm x 773mm x 875mm.</u>			
HE2U	+1 / +4	3.0	4
ME2U	-2 / +2	3.0	4
LE2U	-18 / -22	4.0	4
<b>E3U THREE DOORS 906 litres (32 cu.ft)</b> External dimensions 2476mm x 773mm x 845mm. <u>For remote models 2226mm x 773mm x 875mm.</u>			
HE3U	+1 / +4	3.5	6
ME3U	-2 / +2	3.5	6

Installation of all cabinets and counters require adequate ventilation  
We reserve the right to change the specifications without notice



**Williams Refrigeration Australia Pty Ltd**  
38-42 Gaine Rd Dandenong South Victoria 3175  
Telephone: 03 9799 4900 Facsimile: 03 9799 4911 FreeCall: 1800 338 148  
Email: wra@access.net.au www.williamsref.com.au ABN 25 006 630 084



**Standard and Wide Entry Gastronorm Refrigeration**

Stylish design offering a choice of wide entry or standard gastronorm design combined with an easy to use control panel for excellent temperature control



**Benefits**

- Tough, durable stainless steel exterior and choice of interior finishes
- All cabinets accommodate 1/1 and 2/1 pans
- Easy to clean, hygienic stainless steel base with radius corners and removable shelf supports and racking
- Removable cassette system, for easy servicing and maintenance
- Designed for 43°C ambient environments
- Self closing lockable doors with easy to clean handles
- Heavy duty swivel and brake castors for easy mobility
- CFC free and designed and built to international quality standards
- HACCP compliant



JUL02

## Opal / Emerald

For over 20 years Williams Refrigeration has been a leader in refrigeration technology and design, marketing refrigeration products worldwide. Manufacturing a wide range of products to international quality and construction standards, Williams has gained a global reputation for strength, quality and reliability.

### Features

#### Construction

Designed and manufactured to the highest specification meeting international quality standards, and easy to clean moulded handles.

- Tough stainless steel exterior and interior with radius corners for easy cleaning and durability
- Easy to position adjustable racking to suit your needs
- Easy to remove shelf supports, drawers and complete runner assembly make cleaning and maintenance easy
- Self closing lockable doors with 90° dwell and easy to change magnetic seal
- Swivel and brake castors or adjustable legs
- 75mm CFC free insulation

#### Refrigeration

Leading the way in refrigeration technology the counters are CFC free and designed for efficient and cost effective operation.

- Forced air refrigeration system contained in a removable cassette for easy servicing and maintenance
- Automatic defrost - off cycle above +1°C
- Waste heat recovery vaporiser
- Digital temperature controller
- 240 volt 50 cycle single phase unit complete with fitted plug



### Controls

Control panel incorporates many features to ensure excellent temperature control and effective, easy to manage operation even in the busiest environment. Ensuring operation even if the Control Probe fails, the Control panel features:

- Adjustable operating temperature for maximum effectiveness even in the hottest environment
- Auto/Manual Defrost and Defrost indicator

Counter continues to function even if the Control Probe fails

### Options

- Remote refrigeration system
- Drawers, Glass doors and pass thru models (high temp only)
- Open well (high temp only)
- Ducted airwell (high temp only)
- Blown airwell (high temp only)
- Adjustable legs in lieu of castors

