



Lowline Refrigerator Range



Jarrah

Benefits

- Standard drawer frame accommodates either 2 x 1/1 or 1 x 2/1 gastronorm pans in both models
- 304 grade stainless steel interior and exterior except rear and under
- Includes integral thermal insulating barrier to deflect heat from cooking unit
- Adjustable digital thermostat for flexible cooling and accuracy
- Self contained or remote cabinet
- Four drawer available remote only
- 100% CFC free polyurethane foam for greater insulation and added strength
- Rated for 43°C ambient working conditions.



JL2R



JL2U



JL4R



Model	Temp°C	Amp	Pan Capacity
2 Drawer: External dimensions 1030mm/1400mm x 650mm x 640mm			
JL2R	+1/+4	0.5	2 x 1/1 per drawer
JL2U	+1/+4	2.5	2 x 1/1 per drawer

4 Drawer: External dimensions 1820mm x 650mm x 640mm			
JL4R	+1/+4	0.3	2 x 1/1 per drawer

Williams Refrigeration reserve the right to change specifications without notice.

Controls

- Digital microprocessor control with adjustable electronic thermostat and defrost interval to ensure excellent temperature control.

Construction

- Designed and manufactured to international quality standards
- Stainless steel interior and exterior except rear and under
- Pan holding frame standard
- Frame will accommodate 2 x 1/1 or 1 x 2/1 100mm deep gastronorm pans
- 2 x 1/1 100mm pans per drawer included
- Supplied on castors for mobility (reduces height by 30mm). Legs included for remote models.

Refrigeration

Self Contained (2 drawer only):

- Forced air refrigeration system
- 240 volt single phase power
- 43°C ambient operation
- Waste heat condensate tray

Remote:

- Forced air refrigeration system
- 240 volt single phase power
- Left hand services only
- Supplied with evaporator, tx valve and digital thermostat
- Refrigerant pipes and drain exit out through rear of cabinet unless otherwise specified.

Options

- Full drawer base available
- Locking tabs.

