



Rotel 2 Mini Rotel Oven

Bakery



The Mini Rotel is a compact oven that can be used to produce an extensive range of bakery products.

Features & Benefits

Rotel 2

- Each chamber is individually controlled
- Control panel located front right side
- All instrumentation recessed and guarded
- Inbuilt live steaming system fitted to all chambers

- Bake timers fitted to all chambers
- Interior lamps fitted standard to all chambers
- Tempered glass panels in doors as standard 10mm thick

Rotel 2 Mini Rotel Oven

TECHNICAL DATA

Overall Construction

- Internal baking chambers stainless steel
- Facia & doors stainless steel
- Side and rear of oven colorbond
- Turntable drive system top mounted
- Casters fitted as standard

Operation

- Separate temperature controller for each deck
- Timer 0 - 60 minutes
- Fixed steam duration
- Top & bottom element control to standard decks
- Balance control fitted to all split decks
- Steam ducting / venting fitted to all chambers
- Turntable rotation drive on independent switch

Options

- Steel plates or ceramic soles for sole bread baking
- High crowns up to 300mm (only available some models)



Split Deck - two turntables within the one baking chamber

Model Number	Deck Configuration	Tray Capacity	Loaf Capacity	Dimensions (mm-wxdxh)	Weight (Kilograms)	Electrical Specifications
R616	2 deck, 1 split	6tray, 16"	39	1390x 1405 x 2195	650kg	3P + N + E, 400-415V, 50Hz, 19.5kW
R1016	3 deck, 2 split	10 tray, 16"	63	1390x 1405 x 2060	900kg	3P + N + E, 400-415V, 50Hz, 27kW
R1216	3 deck, 3 split	12 tray, 16"	54	1390x 1405 x 2180	980kg	3P + N + E, 400-415V, 50Hz, 30kW
MR4D16	4 deck standard	8 tray, 16"	60	1390x 1405 x 2210	1170kg	3P + N + E, 400-415V, 50Hz, 26kW
MR4D2S16	4 deck, 2 split	12 tray, 16"	78	1390x 1405 x 2450	1200kg	3P + N + E, 400-415V, 50Hz, 32kW
R618	2 deck, 1 split	6 tray, 18"	39	1490x 1510 x 2195	690kg	3P + N + E, 400-415V, 50Hz, 19.5kW
R1018	3 deck, 2 split	10 tray, 18"	63	1490x 1510 x 2060	940kg	3P + N + E, 400-415V, 50Hz, 27kW
R1218	3 deck, 3 split	12 tray, 18"	54	1490x 1510 x 2180	1020kg	3P + N + E, 400-415V, 50Hz, 30kW
MR4D18	4 deck standard	8 tray, 18"	60	1490x 1510 x 2210	1420kg	3P + N + E, 400-415V, 50Hz, 26kW
MR4D2S18	4 deck, 2 split	12 tray, 18"	78	1490x 1510 x 2451	1275kg	3P + N + E, 400-415V, 50Hz, 32kW

In line with policy to continually develop and improve its products, Moffat reserves the right to change specifications and design without notice.

National Sales Hotline
Toll Free 1800 023 953

Melbourne
740 Springvale Road
Mulgrave, Victoria 3170
Telephone (613) 9518 3888
Facsimile (613) 9518 3833
Email: vsales@moffat.com.au

Sydney
Telephone (612) 8833 4111
Facsimile (612) 8833 4122
Email: nswsales@moffat.com.au

Perth
Telephone (618) 9202 6820
Email: vsales@moffat.com.au

Adelaide
Telephone 1800 023 953
Facsimile (613) 9518 3833
Email: vsales@moffat.com.au

Brisbane
Telephone (617) 3630 8600
Facsimile (617) 3630 8623
Email: qldsales@moffat.com.au

Christchurch, New Zealand
Telephone (643) 389 1007
Facsimile (643) 389 1276
Email: sales@moffat.co.nz
Web: www.moffat.co.nz

Auckland, New Zealand
Telephone (649) 574 3150
Facsimile (649) 574 3159
Email: sales@moffat.co.nz
Web: www.moffat.co.nz

National 24 Hour Service Hotline
(Australia Wide)
Toll Free 1800 622 216

Replacement Parts
(Australia Wide)
Toll Free 1800 337 963

