

## **BREMA G1000A**

#### **MODULAR ICE FLAKE MACHINE**

Brema's G range of modular ice flaker heads produces granular ice flakes which automatically drop into a separate Brema storage bin.

The Brema G1000A is a modular ice flaking machine that produces 1000kg of granular ice per 24 hours and is designed to fit on top of a range of Brema storage bins with differing capacities from 500kg to 550kg. The G1000A can also be installed directly on top of cool rooms.

Granular ice is ideal for exhibiting and presenting foods as well as for use in medical industries. The ice has a fast and efficient refrigerating effect and is easy to handle and dose.



#### STANDARD FEATURES

- 1000kg production per 24 hours
- Can be installed on top of storage bins with capacities between 500kg and 550kg
- Can be installed directly on top of cool rooms
- Produces compact, granular flakes
- Production rated at 21°C air and 15°C water
- Hospital grade stainless steel outer
- Electromechanical operation
- Powerful gear motor and auger system



SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

# From the world of Comcater!


National Head Office 156 Swann Drive Derrimut VIC 3030 Tel: +61 3 8369 4600 Fax: +61 3 8369 4695

Melbourne 96-100 Tope Street, South Melbourne VIC 3205 Tel: +61 3 8369 4600 Fax: +61 2 8699 1299 **Sydney** 20/4 Avenue of the Americas Newington, NSW 2127 Tel: +61 2 9748 3000 Fax: +61 2 9 648 4762 Brisbane 1/62 Borthwick Avenue Murarrie QLD 4172 Tel: +61 7 3399 3122 Fax: +61 7 3399 5311



### **BREMA G1000A**





#### **DIMENSIONS**

934W x 684D x 700H mm

#### **CONNECTIONS**

Water inlet, Water outlet & Electical connection

#### **USABLE BINS**

BIN550 V DS, DRB500

#### **TECHNICAL DATA**

Production 24h	1000 kg	
Cooling System	Air	
Ice Tyoe	Granular	
Refrigerant	R404A	
<b>Electrical Consumption</b>	3200W	
Power Requirements	415V 15amp	3P
Weight	172 kg	

#### **STANDARD ACCESSORIES**

- Water Inlet Hose
- Drainage hose
- External Water Filter
- Pressure Limiting Valve

CONNECTIONS	W	Н
Water inlet	372 mm	187 mm
Water outlet	337 mm	60 mm
Electrical connection	358 mm	257 mm
Clearances	Rear: 100 mm	Sides: 100 mm

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.



PROUDLY DISTRIBUTED BY: