

SK-2 SERIES

Premium Range

SKOPE®

Display / Top Mount

These popular and dependable range of chillers have gained an enviable reputation for offering great performance and reliability.

Options

Additional shelves
Gravity feed shelves
Door lock kit
Sign replacement panel

Double Low/E Argon
Heated glass
Solid doors
Treated coil

Illuminated sign or optional
sign replacement panel

Available in white, black &
stainless steel (additional
cost applies on S/S)

Self-closing, reversible,
double-glazed toughened
safety glass doors

Replaceable, long life
magnetic door gaskets

+1°C to +4°C in 43°C ambient
makes it ideal for use in
high ambient temperatures

Electronic controller
maintains precise
temperature

Energy efficient,
long-life LED lights

Easy, plug-in 10
Amp supply

Front locking swivel
castors for easy
installation and cleaning

SK1000-2



Warranty
2 year protection



**High Energy
Efficiency**


High Energy
Efficiency models available

Specifications

SK-2 Series

Display / Top Mount

SKOPE®




SK650 - GLASS DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	White (AU\$)	S/S (AU\$)	
SK650	173	Integral	Chiller	4,490	5,415	Gross Volume 610 litres Total Shelf Area 1.76m ² (inc. floor) Floor Area 0.52m ²
SK650r	153	Remote	Chiller	4,200	5,125	
	External (mm)		Internal (mm)			
Height*	2195		1570			
Width	740		640			
Depth	700		555			

- 7.40 MEPS (kWhr/24hr/m²)
- Remote refrigeration duty 600 Watts at -5°C SST
- Minimum 200mm clear ventilation space required above cabinet top



SK650
1 DOOR




SK1000 - GLASS DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	White (AU\$)	S/S (AU\$)	
SK1000	227	Integral	Chiller	5,085	6,400	Gross Volume 980 litres Total Shelf Area 2.78m ² (inc. floor) Floor Area 0.79m ²
SK1000r	207	Remote	Chiller	4,670	5,985	
	External (mm)		Internal (mm)			
Height*	2195		1570			
Width	1130		1030			
Depth	700		555			

- 10.10 MEPS (kWhr/24hr/m²)
- Remote refrigeration duty 900 Watts at -5°C SST
- Minimum 200mm clear ventilation space required above cabinet top



SK1000
2 DOOR




SK1300 - GLASS DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	White (AU\$)	S/S (AU\$)	
SK1300	270	Integral	Chiller	7,795	9,435	Gross Volume 1310 litres Total Shelf Area 3.86m ² (inc. floor) Floor Area 1.04m ²
SK1300r	250	Remote	Chiller	7,315	8,960	
	External (mm)		Internal (mm)			
Height*	2195		1570			
Width	1480		1380			
Depth	700		555			

- 9.03 MEPS (kWhr/24hr/m²)
- Remote refrigeration duty 940 Watts at -5°C SST
- Minimum 200mm clear ventilation space required above cabinet top



SK1300
2 DOOR




SK1500 - GLASS DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	White (AU\$)	S/S (AU\$)	
SK1500	300	Integral	Chiller	8,660	10,435	Gross Volume 1536 litres Total Shelf Area 4.35m ² (inc. floor) Floor Area 1.19m ²
SK1500r	260	Remote	Chiller	8,010	9,795	
	External (mm)		Internal (mm)			
Height*	2195		1570			
Width	1706		1606			
Depth	700		555			

- 12.24 MEPS (kWhr/24hr/m²)
- Remote refrigeration duty 1190 Watts at -5°C SST
- Minimum 200mm clear ventilation space required above cabinet top



SK1500
3 DOOR



SK2000 - GLASS DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	White (AU\$)	S/S (AU\$)	
SK2000	360	Integral	Chiller	11,205	14,060	Gross Volume 1825 litres Total Shelf Area 5.17m ² (inc. floor) Floor Area 1.55m ²
SK2000r	320	Remote	Chiller	10,560	13,415	
	External (mm)		Internal (mm)			
Height*	2195		1560			
Width	2220		2070			
Depth	700		520			

- Remote refrigeration duty 1360 Watts at -5°C SST
- Minimum 200mm clear ventilation space required above cabinet top



SK2000
3 DOOR

*Height includes castors or legs