

PEGASUS SERIES

Premium Range

SKOPE®

Food Service / Upright

Designed to be dependable, these upright chillers and freezers incorporate both 1/1 & 2/1 standard Gastronorm tray and shelf width/depth dimensions, enabling integration with other catering equipment.

Options

Extra shelf & slides
Adjustable legs (150-180mm)

Door activated interior
LED lighting with key
locks on all doors

Replaceable, long life
magnetic door gaskets

Energy efficient
refrigeration and insulation
products

5 levels of non-
tip adjustable and
removable
tray slides

Fitted with adjustable
front- locking castors

Electronic controller with
simple to use digital
temperature display

Consistent temperature
maintained by fan-forced
ducted airflow

Self closing and self
sealing doors

Heated fascia to
eliminate condensation



PG1300VC



Warranty
2 year protection





PSF0001

Specifications

Pegasus Series

Food Service / Upright

SKOPE®



PG600VC / PG600VF - 1/1 & 2/1 GASTRONORM TRAYS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	White (AU\$)	S/S (AU\$)	
PG600VC	193	Integral	Chiller	N/A	6,290	Gross Volume 586 litres (20.69ft ³) Total Shelf Area 1.6m ² (excludes base) Floor Area 0.56m ² (integral) 0.56m ² (remote)
PG600VCr	178	Remote	Chiller	N/A	5,945	
PG600VF	215	Integral	Freezer	N/A	8,155	
PG600VFr	195	Remote	Freezer	N/A	7,675	
	External (mm)	Internal (mm)				
Height*	2122-2137	1520				
Width	685	565				
Depth	820	650				

- Chiller remote refrigeration duty 600 Watts at -5°C SST
- Freezer remote refrigeration duty 695 Watts at -30°C SST
- Minimum 200mm clear ventilation space required above cabinet top (integral only)
- Minimum 50mm clear ventilation space required above cabinet top (remote only)
- +1°C to +4°C in 43°C ambient (chiller only)
- -18°C to -21°C in 43°C ambient (freezer only)

PG600VC / PG600VF
1 DOOR

PG1300VC / PG1300VF - 1/1 & 2/1 GASTRONORM TRAYS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	White (AU\$)	S/S (AU\$)	
PG1300VC	230	Integral	Chiller	N/A	8,555	Gross Volume 1298 litres (45.84ft ³) Total Shelf Area 3.19m ² (excludes base) Floor Area 1.11m ² (integral) 1.11m ² (remote)
PG1300VCr	210	Remote	Chiller	N/A	8,125	
PG1300VF	290	Integral	Freezer	N/A	10,875	
PG1300VFr	260	Remote	Freezer	N/A	10,245	
	External (mm)	Internal (mm)				
Height*	2122-2137	1520				
Width	1370	1250				
Depth	820	650				

- Chiller remote refrigeration duty 1000 Watts at -5°C SST
- Freezer remote refrigeration duty 1070 Watts at -30°C SST
- Minimum 200mm clear ventilation space required above cabinet top (integral only)
- Minimum 50mm clear ventilation space required above cabinet top (remote only)
- +1°C to +4°C in 43°C ambient (chiller only)
- -18°C to -21°C in 43°C ambient (freezer only)

PG1300VC / PG1300VF
2 DOOR

*Height includes adjustable castors (115 - 130mm)