



Electrolux

Warewashing Small Pot & Pan Washer with Drain Pump & Detergent Dispenser, High Opening

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



Supplied with: n. 1 basket in stainless steel and n. 1 rack for containers and trays.

Warewashing

Small Pot & Pan Washer with Drain Pump & Detergent Dispenser, High Opening

506050 (EPPWEHG)

Electric small pot&pan washer with electronic control, drain pump, detergent and rinse aid dispenser, high opening

Short Form Specification

Item No. _____

304 AISI stainless steel front and side panels, wash tank, tank filter and wash and rinse arms. Double skinned insulated door divided in 2 parts with 180° frontal opening. N. 4 washing cycles.

Built-in atmospheric, insulated water boiler (10,5 kW), 18-liter capacity, combined with rinse booster pump guarantee a constant hot rinse temperature of 84°C. Boiler with 304 welding for protection against corrosion.

Wash Safe Control assures the correct water temperature and pressure during the rinse phase to guarantee a perfect rinsing performance independent from the water pressure in the network (min. 0,5 bar).

High efficiency air gap (class A) in water inlet circuit to avoid water being syphoned back into the network as a result of a sudden drop in mains pressure.

Fault auto-diagnosis system. Self-cleaning cycle. Drain pump, rinse aid and detergent dispenser included.

Pre-arrangements for connection to an Energy Management device and to an automatic detergent dispenser.

Cell dimensions mm670x710x710h.

Load capacity: n.3x1/1 GN or 3 trays mm600x800.

For front-feed loading. IPX5 water protection.

APPROVAL: _____



Electrolux

Warewashing
Small Pot & Pan Washer with Drain Pump & Detergent Dispenser, High
Opening

Main Features

- Atmospheric insulated boiler combined with the rinse booster pump for perfect rinsing results (water temperature and pressure always constant during rinsing cycles), independent from the inlet water pressure.
- Green light of "WASH SAFE CONTROL" confirms that items have been rinsed properly.
- High efficiency air gap (class A) in water inlet circuit to avoid water being siphoned back into the network as a result of a sudden drop in main pressures.
- Open air gap in compliance with WRC regulations.
- 4 washing programs (one program is continual).
- Equipped with drain pump and built-in detergent dispenser for easy and quick installation without opening the machine.
- Easier access to the washing chamber thanks to the 180° frontal opening door.
- Requires limited space for opening thanks to the door divided in 2 sections.
- Self-cleaning cycle.
- Low noise level.
- Simple electronic control panel.
- Fault auto-diagnosis system.
- Simple service from the front.

Construction

- 304 stainless steel boiler with higher welding protection to increase resistance to corrosion.
- External connecting board protected by a waterproof plastic box.
- Unit to feature smooth surfaces to facilitate cleaning.
- Easy to remove pump and tank filters.
- Large strainer box above the water surface for frequent cleaning operations.
- Double skin insulated door to reduce heat dispersion.
- Equipped with side washing arms in addition to upper and lower wash arms.
- Pre-arranged to be connected to Energy Management device.
- Available upon request, pre-arranged model for HACCP implementation (both basic as well as integrated system).
- 304 AISI stainless steel front and side panels, wash tank, tank filter and wash and rinse arms.
- Unit to feature rinse aid dispenser pump.


Included Accessories

- 1 of Extra rack for containers and trays PNC 864182
- 1 of Stainless steel basket for pot washer, 688mm PNC 864191


Optional Accessories

- Integrated HACCP kit PNC 864001
- HACCP printer kit PNC 864002
- Filter for partial demineralization PNC 864017
- Kit to measure total and partial water hardness PNC 864050
- Extra rack for containers and trays PNC 864182
- Stainless steel basket for pot washer, 688mm PNC 864191
- Filter for total demineralization PNC 864367

Front




Top



- | | |
|----------------------------|---------------------------|
| AV = Air vents | XD = Detergent connection |
| D = Drain | XR = Rinse aid connection |
| EI = Electrical connection | |
| EQ = Equipotential screw | |
| H-
WI = Hot water inlet | |
| WI = Water inlet | |

Side



Electric

Supply voltage:	
506050 (EPPWEHG)	400 V/3N ph/50 Hz
Default Installed Power:	13 kW
Electrical power:	20 kW

Water:

Pressure, bar min/max:	0.5-7 bar
Water supply temperature:	50 °C
Boiler Capacity (lt):	18
Washing cycle temperature:	55-65 °C
Washing tank capacity (lt):	95
Washing cycle pump power:	2.5 kW
Washing cycle electrical elements:	7 kW
Hot rinse cycle duration (sec.):	20
Hot rinse cycle temperature:	84 °C

Key Information:

N° of working cycles - sec.:	4 (180/360/540/inf)
External dimensions, Height:	1991 mm
External dimensions, Width:	876 mm
External dimensions, Depth:	900 mm
Net weight:	216 kg
Shipping weight:	255 kg
Shipping height:	2230 mm
Shipping width:	1030 mm
Shipping depth:	1070 mm
Shipping volume:	2.46 m ³
Cell dimensions - width:	670 mm
Cell dimensions - depth:	710 mm
Cell dimensions - height:	740 mm
Rinsing water consumption (per cycle):	7 lt