

THE MOST VERSATILE HOLDING CABINET ON THE MARKET!

Electric or non-electric
transporter holds GN food
pans, sheet pans, trays and
pizza boxes all in one!



NON-ELECTRIC:

- Passive hot or cold holding for 4 hours or more.
- Durable, rust-free, dent-free, one-piece molded polyethylene body filled with polyurethane foam insulation that easily holds food at safe temperatures and out of the danger zone.
- Adjustable stainless steel Universal rails take the guesswork out of choosing different rail systems each time.

ELECTRIC: Features all of the above PLUS

- Separate, dual compartments with heaters on one or both doors maximize food quality and menu flexibility. (Tall cart)
- Available in energy-efficient 110V and 220V models.

CAMBRO
TRUSTED FOR GENERATIONS™



www.cambro.com

the NEW Combo Cart TM Plus

NON-ELECTRIC

Non-electric holds hot or cold foods for 4 hours or more.

Holds GN food pans, sheet pans, trays and pizza boxes!

MARINE RAILING

Creates a bonus staging area for food pans.

STANDARD 15 x 3,2 CM CASTERS

High-Performance, all swivel with brakes for smooth positioning and navigation; non-marking.



12,7 x 20,3 CM MENU POCKET

Allows for easy product ID with either an index card or by writing directly onto smooth surface with a grease pencil.

WIDE PADDLE LATCHES

For easy opening and closing.

PERIMETER BUMPER

Protects cart and walls.



ERGONOMIC MOLDED-IN HANDLES

Will never break; great for maneuvering by operators of all heights.



GASKET-FREE

Worry-free door! Swings open completely to the side.



POWER ON AND HEAT ON INDICATORS

Communicate the power and heating status of the unit. Know instantly when the compartment has reached target temperature. Turn on and off without unplugging the cord.

The Combo Cart *Plus* is ideal for...

Large events • Applications that require frequent opening and closing • Flexible menu options
Holding and Transport • Operators who demand reliability and durability, under peak performance

ELECTRIC ⚡

Keeps food safely between 65°C to 74°C with convenient, pre-set, gentle, non-radiant heat.

ENERGY-SAVING HEATER

Tall Carts are over 50%, and Low Carts are over 180% more energy efficient than leading metal carts! Gentle, non-radiant heat circulates consistently from front to back of the cabinet.



Electric
Holds hot foods for as long as you need it to.

SOLAR DIGITAL THERMOMETER

Monitor internal cabinet temperature at a glance.

POLYETHYLENE EXTERIOR

Keeps food moist naturally and remains cool to the touch during operation, unlike metal cabinets.

HEAVY DUTY 15 x 5 CM CASTERS


Hi-modulus, non-marking rubber casters.

CORD KEEPER

Stores 2,7 m power cord neatly and safely.

CMBPHHD

CMBPLHHD



INSULATION

CFC-free, polyurethane insulation throughout the body and doors maximizes heat or cold retention for 4 hours or more with no electricity needed.



STAINLESS STEEL UNIVERSAL RAILS

Hold sheet pans, food pans, pizza boxes and trays (or limitless combinations of these!)



RAIL GUIDES

Numbering corresponding to different holding containers helps speed set-up.

Holding Capacity Reference for **NEW COMBO CART™ PLUS**

TYPE OF CONTAINER	LOW STANDARD CAPACITY	LOW MAXIMUM CAPACITY	TALL STANDARD CAPACITY	TALL MAXIMUM CAPACITY
45,7 x 66 CM FULL SIZE SHEET PANS	7	16*	14	32*
33 x 5,7 CM HALF SIZE SHEET PANS	14	32*	28	64*
GN ¼ HOTEL PANS (6,5 CM DEEP)	10	16	20	32
GN ¼ HOTEL PANS (10 CM DEEP)	10	10	20	20
40 x 60 CM TRAYS (LIP LOAD)	7	15*	14	30*
32,5 x 53 CM TRAYS	14	32*	28	64*
PIZZA BOXES 40,6 x 40,6 x 5,1 CM	7	8*	14	16*

Standard rails: 7 pairs/compartment *Additional rails required.

Electrical Specifications (Per Compartment)

	110V MODELS	220V MODELS
REQUIRED VOLTAGE	100-125 VAC	200-230 VAC
MAXIMUM AMP	4.6a	2.3a
WATTS / HEATER	529w	506w
HERTZ	50/60	50/60
PHASE	Single	Single
PLUG TYPES	5-15 to C15RA	CEE7/7 to C15RA
ALTERNATE PLUG TYPES FOR INTERNATIONAL	JIS8303 to C15RA (Japan)	BS1363 to C15RA (UK / Ireland+more)
POWER CORD LENGTH	2,7 m	2,7 m

Pre-heat Time: Approx. 45 min.

Recovery Time: 3 min.



CODE	DESCRIPTION	UNIT WEIGHT	CASE KG. (M³)
Non-Electric Low			
CMBPL	Standard Casters	52,6 kg	60 (0,7)
CMBPLHD	Heavy Duty Casters	56,9 kg	64,3 (0,7)
Non-Electric Tall			
CMBP	Standard Casters	95,3 kg	104,6 (1,2)
CMBPHD	Heavy Duty Casters	99,6 kg	108,9 (1,2)
Electric Low			
CMBPLH / CMBPLH2	110V, Standard Casters / 220V, Standard Casters	58,3 kg	65,7 (0,7)
CMBPLHHD / CMBPLH2HD	110V, Heavy Duty Casters / 220V, Heavy Duty Casters	62,6 kg	70 (0,7)
Electric Tall			
CMBPH / CMBPH2	110V, Standard Casters / 220V, Standard Casters	105,2 kg	114,5 (1,2)
CMBPHHD / CMBPH2HD	110V, Heavy Duty Casters / 220V, Heavy Duty Casters	109,5 kg	118,8 (1,2)
CMBPTH / CMBPTH2	110V, Top Door Heated only, Standard Casters / 220V, Top Door Heated only, Standard Casters	104,6 kg	113,9 (1,2)
CMBPTHHD / CMBPTH2HD	110V, Top Door Heated only, Heavy Duty Casters / 220V, Top Door Heated only, Heavy Duty Casters	108,9 kg	118,2 (1,2)

Case Pack: 1. **Color:** Charcoal Gray (615).

Standard Railing Includes: 7 pairs of stainless steel Universal rails/compartment.

Includes Standard Casters: 15 x 3,2 cm casters.

Options: Security Package (SP) available.

Patent pending.

Exterior Dimensions (Low) W x D x H: 70,2 x 85,1 x 104,5 cm

Exterior Dimensions (Tall) W x D x H: 70,2 x 85,1 x 167,3 cm

Compartment Dimensions W x D x H: 53,7 x 66,7 x 64,8 cm

ACCESSORIES

CASE	DESCRIPTION	UNIT WEIGHT	CASE KG. (M³)
CMBPR1	1 Pair of Rails	1,81 kg	1,87 (0,06)
CMBPR7	7 Pairs of Rails	12,25 kg	12,59 (0,2)



CAMBRO U.S.A.
TEL: (714) 848-1555
FAX: (714) 230-4375
international@cambro.com

CAMBRO EUROPEAN LOGISTICS
TEL: (49) 7022 90 100 0
FAX: (49) 7022 90100 19
cambroeuropa@cambro.com

CAMBRO NORTH IRELAND & UK
TEL: 0800 587 0057 Toll Free
FAX: 0845 280 3411
cambrouk@cambro.com

CAMBRO IRELAND
TEL: 1800 509 046 Toll Free
FAX: 01 633 55 76
cambroireland@cambro.com

