

# HRE-140B UPRIGHT REACH IN REFRIGERATOR



Product Specifications	
WEIGHT	Net: 164kg Packed: 189kg
AC SUPPLY VOLTAGE	220 - 240v / 50Hz / 1
ELECTRIC CIRCUIT PROTECTION	Earth Wire, Circuit Breaker
INTERIOR / EXTERIOR	Stainless Steel / Stainless Steel, Galvanized Steel (Rear, Bottom)
AMPERAGE	2.89A
REFRIGERATION SYSTEM	Forced Air Circulation Interior Fan - DC12V 4W x 1
DEFROST SYSTEM	Off-Cycle
TEMPERATURE CONTROL	Microprocessor (Digital temp. indication) - Adjustable from 0°C to 16°C
DEFROST CONTROL	Microprocessor
DRAIN EVAPORATOR PAN	Stainless steel, 170W
CASTOR	Urethane (76mm DIA, 115mm High)
EFFECTIVE CAPACITY	Approx. 1379L
INSULATION	Polyurethane foam
REFRIGERANT	R134a
HEAT REJECTION	940W at 43°C ambient
AMBIENT TEMPERATURE	5 — 43°C

Product Range		
PART NO.	DESCRIPTION	LIST PRICE
97000002	HRE-140B	\$6615.00

