

COUNTER LINE SERIES

SKOPE®

Standard Range

Display / Under Counter

Available in a range of depths, doors and installation heights, making this series ideal for restaurants, commercial kitchens and foodservice areas with non-gastronorm chiller requirements.

Options

R/H Services
S/S Countertop
Additional shelves
Door lock kit

Double Low/E Argon
Heated glass (swing
door only)
Sliding doors



Warranty
2 year protection



**High Energy
Efficiency**


High Energy
Efficiency models available

Specifications

Counterline Series

Display / Under Counter

SKOPE®



Integral front elevation

1455



Remote front elevation

CL400 - SOLID/GLASS DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	White (AUS)	S/S (AUS)
CL400	127	Integral	Chiller	5,385	6,055
CL400r	112	Remote	Chiller	4,110	4,775

	Integral External (mm)	Remote External (mm)	Internal (mm)
Height*	725	725	545**
Width	1600	1455	1120
Depth***	680	680	565

Gross Volume
390 litres
Total Shelf Area
1.74m² (including floor)
Floor Area
1.09m² (integral)
0.99m² (remote)

CL400
2 DOOR

- 12.75 MEPS (kWh/24hr/m²)
- Remote refrigeration duty 480 Watts at -5°C SST

CL600 - SOLID/GLASS DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	White (AUS)	S/S (AUS)
CL600	140	Integral	Chiller	6,685	7,575
CL600r	125	Remote	Chiller	5,535	6,300

	Integral External (mm)	Remote External (mm)	Internal (mm)
Height*	725	725	545**
Width	2210	2065	1730
Depth***	680	680	565

Gross Volume
600 litres
Total Shelf Area
2.70m² (including floor)
Floor Area
1.50m² (integral)
1.40m² (remote)

CL600
3 DOOR

- 11.65 MEPS (kWh/24hr/m²)
- Remote refrigeration duty 615 Watts at -5°C SST

CL800 - SOLID/GLASS DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	White (AUS)	S/S (AUS)
CL800	153	Integral	Chiller	8,120	9,050
CL800r	138	Remote	Chiller	7,235	8,215

	Integral External (mm)	Remote External (mm)	Internal (mm)
Height*	725	725	545**
Width	2820	2675	2340
Depth***	680	680	565

Gross Volume
810 litres
Total Shelf Area
3.66m² (including floor)
Floor Area
1.92m² (integral)
1.80m² (remote)

CL800
4 DOOR

- 8.74 MEPS (kWh/24hr/m²)
- Remote refrigeration duty 850 Watts at -5°C SST

CC300 - SOLID/GLASS DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	White (AUS)	S/S (AUS)
CC300	122	Integral	Chiller	5,255	5,925
CC300r	107	Remote	Chiller	3,980	4,650

	Integral External (mm)	Remote External (mm)	Internal (mm)
Height*	725	725	545**
Width	1600	1455	1120
Depth***	600	600	485

Gross Volume
335 litres
Total Shelf Area
1.48m² (including floor)
Floor Area
0.96m² (integral)
0.87m² (remote)

CC300
2 DOOR

- 11.65 MEPS (kWh/24hr/m²)
- Remote refrigeration duty 400 Watts at -5°C SST

CC500 - SOLID/GLASS DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	White (AUS)	S/S (AUS)
CC500	135	Integral	Chiller	6,465	7,235
CC500r	120	Remote	Chiller	5,195	5,965

	Integral External (mm)	Remote External (mm)	Internal (mm)
Height*	725	725	545**
Width	2210	2065	1730
Depth***	600	600	485

Gross Volume
517 litres
Total Shelf Area
2.29m² (including floor)
Floor Area
1.33m² (integral)
1.24m² (remote)

CC500
3 DOOR

- 9.83 MEPS (kWh/24hr/m²)
- Remote refrigeration duty 540 Watts at -5°C SST

CC700 - SOLID/GLASS DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	White (AUS)	S/S (AUS)
CC700	148	Integral	Chiller	7,605	8,530
CC700r	133	Remote	Chiller	6,685	7,670

	Integral External (mm)	Remote External (mm)	Internal (mm)
Height*	725	725	545**
Width	2820	2675	2340
Depth***	600	600	485

Gross Volume
700 litres
Total Shelf Area
3.11m² (including floor)
Floor Area
1.70m² (integral)
1.60m² (remote)

CC700
4 DOOR

- Remote refrigeration duty 660 Watts at -5°C SST

*Height excludes castors, legs or optional countertop (20mm) **Smallest available internal height ***Depth excludes optional countertop (20mm)