

BREMA TM250A

MODULAR PEBBLES ICE MACHINE

Brema's TM range of self-contained ice makers produces pebble-shaped ice particles and stores them in a separate storage bin.

The Brema TM250A is a modular pebbles ice machine that produces 250kg of pebbles ice per 24 hours and is designed to fit on top of a range of Brema storage bins with differing capacities from 100kg to 550kg.

Pebbles ice is ideal for crushing, blending and mixing into cocktails, fruit juices, smoothies and frappés. The ice has a fast and efficient refrigerating effect and is easy to handle and dose.



STANDARD FEATURES

- 240kg production per 24 hours
- Can be installed on top of storage bins with capacities between 100kg and 550kg
- Produces pebble-shaped ice
- Production rated at 21°C air and 15°C water
- Hospital grade stainless steel outer
- Electromechanical operation
- Powerful gear motor and auger system



SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

from the world of Comcater!

National Head Office 156 Swann Drive Derrimut VIC 3030 Tel: +61 3 8369 4600 Fax: +61 3 8369 4695

96-100 Tope Street South Melbourne VIC 3205 Tel: +61 3 8369 4600 Fax: +61 3 8699 1299 Sydney
20/4 Avenue of the Americas
Newington, NSW 2127
Tel: +61 2 9748 3000

Fax: +61 2 9648 4762

Brisbane
1/62 Borthwick Avenue
Murarrie QLD 4172
Tel: +61 7 3399 3122
Fax: +61 7 3399 5311


Perth Unit 4/35 Westchester Road Malaga WA 6090 Tel: +61 8 9248 9290

Fax: +61 8 9248 1903



BREMA TM250A





*(4) Water cooled model only - available upon request

DIMENSIONS

640W x 470D x 700H mm

CONNECTIONS

3/4" Water inlet, 24mm Water outlet & Electical connection

USABLE BINS

BIN200, BIN240PE, BIN350, BIN550 V DS, RB100, DRB100, DRB500

TECHNICAL DATA

Production 24h	250 kg
Cooling System	Air
Ice Tyoe	Pebbles
Refrigerant	R404A
Electrical Consumption	1050W
Power Requirements	240V 15amp
Weight	82 kg

STANDARD ACCESSORIES

- Water Inlet Hose
- Drainage hose
- External Water Filter
- Pressure Limiting Valve

CONNECTIONS	W	Н
Water inlet	116 mm	282 mm
Water outlet	34 mm	228 mm
Electrical connection	58 mm	292 mm
Clearances	Rear: 100 mm	Sides: 100 mm

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.



PROUDLY DISTRIBUTED BY: